



## E32-T24S 2M

Fiber optic sensor head, through-beam, cylindrical radial, diameter 3.5 mm, R10 fiber, 2 m cable

# Specifications

<b>Sensing method</b>	Through-beam
<b>Shape</b>	Cylindrical radial
<b>Size</b>	dia 3.5 mm
<b>Application</b>	Object detection, Wafer mapping
<b>Temperature range</b>	-40-70 °C
<b>Sensing distance</b>	4000 mm
<b>Cable length</b>	2 m
<b>Bending radius</b>	10 mm
<b>Free cut</b>	✓
<b>Material core</b>	Plastic
<b>Degree of protection (IP)</b>	IP50
<b>Sensing surface orientation</b>	Side-view
<b>Material sheath</b>	PVC

# Related products



**E3NX-CA**  
High-performance color mark sensor



**E3NX-CA**  
High-performance color mark sensor



**E3NX-FA**  
High-performance digital fiber amplifier



**E3NX-MA**  
Smart Fiber Amplifier Units



**E3X-HD**  
Easy-teach digital fiber amplifier



**E3X-NA**  
Digital fiber amplifier with potentiometer adjustment



**E3X-SD**  
Single display digital fiber amplifier

# Downloads

CAD Library



**Fiber Sensor Selection**  
Selection Guide

EN PDF 51.8 MB

