



P2RF-08-ESS

G2RS socket, 2-pole, DIN-rail/surface-mounting, screw (box type)

Specifications

Applicable product family	G2R-2-S
Mounting method	DIN rail/screw
Depth	61 mm
Height	77.6 mm
Width	15.6 mm
Terminal	Rise-up
Color	Black
Hold down clip included	✘
Release Lever included	✘
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Forked terminals, Round terminals

Fits to



G2R-2-S 110VAC (S)
Relay, plug-in, DPDT, 5 A,
mechanical indicator, 110
VAC



G2R-2-S 12VDC (S)
Relay, plug-in, 8-pin, DPDT,
10 A, mech indicator, label
facility, 12 VDC



G2R-2-S 220VAC (S)
Relay, plug-in, 5 A,
mechanical indicator, 220
VAC



G2R-2-S 230VAC (S)
Relay, plug-in, DPST, 10 A,
mechanical indicator, 230
VAC

**G2R-2-S 24VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 24 VAC

**G2R-2-S 48VDC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 48 VDC

**G2R-2-SD 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech indicators, coil suppressor, label facility

**G2R-2-SN 110VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VDC

**G2R-2-SN 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

**G2R-2-SN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VAC

**G2R-2-SN 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 240 VAC

**G2R-2-SN 48VAC**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VAC

G2R-2-SN-AP3 230VAC (S)

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SN-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SND 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 48 VDC

**G2R-2-SNDI-AP3 24VDC (S)**

Relay, plug-in, 8-pin, SPDT, 5 A, mech & LED indicators, coil suppressor, label test button, Au-plating

**G2R-2-SNI 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 120 VAC

**G2R-2-SNI 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 240 VAC

**G2R-2-SNI 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



G2R-2-SNI-AP3 230VAC (S)

Relay, plug-in, DPDT (gold plated), 5 A, mech. & LED indicator, test button, 230 VAC

Accessories



P2CM-ESS

Clip & release lever for P2RF-**-ESS socket (1 pc = 1 bag including 10 levers)

PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length

PFP-50N

Din rail track, 500 mm



PFP-M

End plate

PFP-S

Spacer



PYC-TR

Labels for P2RF-05/08-ESS socket



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

CAD Library



P2RF-08-ESS Relay Sockets

Datasheet

EN PDF 480 KB