



## P2RFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals

# Specifications

Applicable product family	G2R-2-S, K7L
Mounting method	DIN rail/screw
Depth	61.0 mm
Height	79 mm
Width	15.5 mm
Terminal	Screw
Color	Black
Hold down clip included	✓
Release Lever included	✓
Applicable ferrules	Forked terminals, Round terminals

## Fits to



### G2R-2-S 110VAC (S)

Relay, plug-in, DPDT, 5 A, mechanical indicator, 110 VAC



### G2R-2-S 12VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 12 VDC



### G2R-2-S 220VAC (S)

Relay, plug-in, 5 A, mechanical indicator, 220 VAC



### G2R-2-S 230VAC (S)

Relay, plug-in, DPST, 10 A, mechanical indicator, 230 VAC

**G2R-2-S 24VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 24 VAC

**G2R-2-S 48VDC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 48 VDC

**G2R-2-SD 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech indicators, coil suppressor, label facility

**G2R-2-SN 110VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VDC

**G2R-2-SN 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

**G2R-2-SN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VAC

**G2R-2-SN 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 240 VAC

**G2R-2-SN 48VAC**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VAC

**G2R-2-SN-AP3 230VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SN-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SND 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 48 VDC

**G2R-2-SNDI-AP3 24VDC (S)**

Relay, plug-in, 8-pin, SPDT, 5 A, mech & LED indicators, coil suppressor, label test button, Au-plating

**G2R-2-SNI 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 120 VAC

**G2R-2-SNI 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 240 VAC

**G2R-2-SNI 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



**G2R-2-SNI-AP3  
230VAC (S)**

Relay, plug-in, DPDT (gold plated), 5 A, mech. & LED indicator, test button, 230 VAC

# Accessories



**MG-CPM-04 41390N**

White modular sheet with 48 marker of size mm: 5x10, Polycarbonate, Halogen Free, Silicon Free, UL94 V0, -40° to 130°C, Minimum Order Quantity is 1 box (In one box: 35 sheets, total markers 1680)



**P2DN-15.7-100S**

Box of short bar for P2RFZ-E. In the box there are 10pcs of short bar, 15.7 mm pitch, 10 pole (10 terminal) and 20pcs of caps. Color is blue.



**P2DN-6.8-100S**

Box of short bar for P2RFZ-E. In the box there are 10pcs of short bar, 6.8 mm pitch, 10 pole (20 terminal) and 20pcs of caps. Color is blue.



**P2DN-CP100**

Box of 100 caps for P2DN short bar: insulation cap for the short bar cut, blue color

**PFP-100N**

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

**PFP-100N2**

DIN-rail mounting track, 35x16mm, 1m length

**PFP-50N**

Din rail track, 500 mm



**PFP-M**

End plate

**PFP-S**

Spacer



**XW5Z-EP12**

Separator Plate for terminal blocks, 12 mm width



**XW5Z-EP6**

End bracket for terminal blocks, 6 mm width

CAD Library



**G2R-\_S (S) General-purpose Relay**  
**Datasheet**

EN PDF 3.88 MB